FORMAT: USA MATERIAL SAFETY DATA SHEET

PRODUCT: GE50.08 WINDOW & DOOR CAULK (GRAY)

-----

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

\_\_\_\_\_\_

MANUFACTURED BY: SUPPLIED BY:

GE SILICONES GE SILICONES

260 HUDSON RIVER ROAD 260 HUDSON RIVER ROAD

WATERFORD, NY 12188 WATERFORD, NY 12188

EMERGENCY PHONE (24 HRS) EMERGENCY PHONE (24 HRS)

(518) 237-3330 (518) 237-3330

REVISED: 01/30/03

PREPARER: B. JAVOREK

CHEMICAL FAMILY/USE: SILICONE RUBBER SEALANT

FORMULA: MIXTURE

2. COMPOSITION/INFORMATION ON INGREDIENTS

-----

PRODUCT COMPOSITION/ APPROX. ACGIH TLV OSHA PEL

CAS REG NO. WGT. % TWA STEL TWA STEL UNITS

HAZARDOUS

METHYLTRIMETHOXYSILANE

1185-55-3 1-5 200(R) NE 200(R) NE PPM

HEXAMETHYLDISILAZANE

999-97-3 1-5 25(R) NE 35STEL NE (R) PPM

DISTILLATES, PETROLEUM, HYDROTREATED

LIGHT

64742-47-8 5-10 NE NA NE NA NA

### 2. NON-HAZARDOUS

ME-DIMETHOXY/STPD POLYDIME-SILOXANE

68037-58-1 30-60 NE NE NE NE NA

DIMETHYLPOLYSILOXANE

63148-62-9 10-30 NE NA NE NA NA

TETRAMER TREATED FUMED SILICA

68583-49-3 10-30 10 NE 15 NE MG/M3

See Section 15 for description of any WHMIS Trade Secret(s).

### 3. HAZARDS IDENTIFICATION

------

# 1 EMERGENCY OVERVIEW:

### WARNING!

May be harmful if swallowed, inhaled, or absorbed through skin.

Irritating to skin, eyes, and respiratory tract.

May cause central nervous system depression.

Ammonia odor

Gray solid

POTENTIAL HEALTH EFFECTS:

INGESTION:

May be harmful if swallowed.

May cause central nervous system effects.

May cause gastrointestinal irritation, nausea, vomiting, and  $\operatorname{diarrhea}$ .

SKIN CONTACT:

Uncured product contact will irritate lips, gums and tongue.

Uncured product contact may irritate the skin.

May be absorbed through skin and produce effects as listed  $\mbox{under "Ingestion"}.$ 

INHALATION:

Causes mild respiratory irritation.

Applies only in uncured state.

EYE CONTACT:
Uncured product contact irritates eyes.
MEDICAL CONDITIONS AGGRAVATED:
Pre-existing skin or respiratory diseases.
SUBCHRONIC (TARGET ORGAN) EFFECTS:
Central nervous system
Skin
CHRONIC EFFECTS/CARCINOGENICITY:
This product or one of its ingredients present 0.1% or more
is NOT listed as a carcinogen or suspected carcinogen by
NTP, IARC, or OSHA.
PRODUCTS/INGREDIENTS
This space reserved for special use.
PRINCIPLE ROUTES OF EXPOSURE:
Oral.
Dermal - skin.
Eyes.
Inhalation.
Absorption through skin.
OTHER:
Methanol released during curing.
This product contains methylpolysiloxanes which can generate
formaldehyde at approximately 300 degrees Fahrenheit (150'C)
and above, in atmospheres which contain oxygen. Formaldehyde
is a skin and respiratory sensitizer, eye and throat irritant,
acute toxicant, and potential cancer hazard. An MSDS for
formaldehyde is available from GE Silicones.
1
4. FIRST AID MEASURES
INGESTION:

page: 3

COPYRIGHT GENERAL ELECTRIC CO.

May also cause other effects as listed under "Ingestion".

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

### SKIN:

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.

Get medical attention if irritation persists.

### INHALATION:

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

## EYES:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN:

None known.

\_\_\_\_\_\_

# 5. FIRE FIGHTING MEASURES

\_\_\_\_\_

FLASH POINT: NA (C) NA (F)

METHOD : NA

IGNITION TEMP : UNKN (C) UNKN (F)

FLAMMABLE LIMITS IN AIR - LOWER (%): NA
FLAMMABLE LIMITS IN AIR - UPPER (%): NA
SENSITIVITY TO MECHANICAL IMPACT (Y/N): NO

SENSITIVITY TO STATIC DISCHARGE:

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA:

All standard firefighting media

SPECIAL FIREFIGHTING PROCEDURES:

Firefighters must wear NIOSH/MSHA approved positive pressure

6. ACCIDENTAL RELEASE MEASURES
ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
Wipe, scrape or soak up in an inert material and put in a
container for disposal.
Wash walking surfaces with detergent and water to reduce slip-
ping hazard.
Wear proper protective equipment as specified in the protective
equipment section.
7. HANDLING AND STORAGE
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
Keep container closed when not in use.
Avoid contact with skin and eyes.
Use only in a well ventilated area.
Remove contact lenses before using sealant. Do not handle
lenses until all sealant has been cleaned from the finger-
tips, nails and cuticles. Residual sealant may remain on
fingers for several days and transfer to lenses and cause
severe eye irritation.
Product releases methanol during application and curing.
Product releases ammonia during application and curing.

self-contained breathing apparatus with full face mask and full

protective clothing.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

\_\_\_\_\_\_

## ENGINEERING CONTROLS:

Showers and eyewash stations. See "Ventilation" below.

RESPIRATORY PROTECTION:

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29 CFR 1910.134).

PROTECTIVE GLOVES:

Cloth gloves.

EYE AND FACE PROTECTION:

Safety glasses.

OTHER PROTECTIVE EQUIPMENT:

Wear eye protection and protective clothing.

VENTILATION:

Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

-----

1

PRODUCT INFORMATION:

BOILING POINT : NA (C) NA (F)

VAPOR PRESSURE(20 C)(MM HG): NA
VAPOR DENSITY (AIR=1): NA

FREEZING POINT : NA (C) NA (F)

COPYRIGHT GENERAL ELECTRIC CO.

MELTING POINT : NA (C) NA (F)

PHYSICAL STATE : SOLID
ODOR : AMMONIA

COLOR : NEUTRAL GRAY

ODOR THRESHOLD (PPM) : 46.8
% VOLATILE BY VOLUME : NA

EVAP. RATE(BUTYL ACETATE=1): <1

SPECIFIC GRAVITY (WATER=1) : 1.05

DENSITY (KG/M3) : 1048

ACID/ALKALINITY (MEQ/G) : UNKNOWN

PH : NA

VOC EXCL.H20 & EXEMPTS(G/L): 27

SOLUBILITY IN WATER (20 C) : INSOLUBLE

SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT): PARTIALLY IN TOLUENE

\_\_\_\_\_\_

#### 10. STABILITY AND REACTIVITY

-----

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARDOUS THERMAL DECOMPOSITION/COMBUSTION PRODUCTS:

Carbon monoxide.

Carbon dioxide.

Silicon dioxide.

Methanol.

Ammonia.

INCOMPATIBILITY (MATERIALS TO AVOID):

None known.

CONDITIONS TO AVOID:

Vapor and/or liquid react with water to form ammonia.

\_\_\_\_\_

## 11. TOXICOLOGICAL INFORMATION

COPYRIGHT GENERAL ELECTRIC CO.

PRODUCT INFORMATION:
ACUTE ORAL LD50 (MG/KG): UNKNOWN
ACUTE DERMAL LD50 (MG/KG): UNKNOWN
ACUTE INHALATION LC50 (MG/L): UNKNOWN
OTHER:
None.
AMES TEST: UNKNOWN
12. ECOLOGICAL INFORMATION
ECOTOXICOLOGICAL INFORMATION: No data at this time
CHEMICAL FATE INFORMATION: No data at this time
CALIFICIAL FAIR TAZONIA FIONICA NO GREEK GENERAL CALIFORNIA FIONICA CONTROL CALIFORNIA C
13. DISPOSAL CONSIDERATIONS
13. DISFORM CONSIDERATIONS
DIGDOCAL MERILOD.
DISPOSAL METHOD:
Disposal should be made in accordance with federal, state and
local regulations.
14. TRANSPORT INFORMATION

DOT SHIPPING NAME: NONE

DOT HAZARD CLASS: NOT DOT REGULATED

DOT LABEL(S): NONE
UN/NA NUMBER: NONE
PLACARDS: NONE

IATA:

NOT REGULATED BY IATA

IMO IMDG-code: NOT REGULATED FOR OCEAN TRANSPORTATION

EUROPEAN CLASS:

RID (OCTI): NONE

ADR (ECE): NONE

EMS No: NA

RAR (IATA): NONE

\_\_\_\_\_\_

# 15. REGULATORY INFORMATION

------

SARA SECTION 302:

None Found

SARA (311,312) HAZARD CLASS:

ACUTE HEALTH HAZARD

SARA (313) CHEMICALS:

NONE

CPSC CLASSIFICATION: NA

WHMIS HAZARD CLASS:

D2A VERY TOXIC MATERIALS

D2B TOXIC MATERIALS

WHMIS TRADE SECRET:

None

EXPORT:

SCHDLE B/HTSUS: 3910.00 Silicones in Primary Form

ECCN: EAR99

COPYRIGHT GENERAL ELECTRIC CO.

HAZARD RATING SYSTEMS

HMIS FLAMMABILITY 0 , REACTIVITY 0 , HEALTH 1

NFPA HEALTH = 1, FLAMMABILIITY = 0 , REACTIVITY = 0

CALIFORNIA PROPOSITION 65:

NONE

------

16. OTHER INFORMATION

-----

This product or its components are on the European inventory of existing commercial chemicals (EINECS).....

.....

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

This product or its components are on the Australian inventory

(ACOIN).....

.....

NA = not applicable UNKN = unknown

 ${\tt NE}$  = none established  ${\tt REC}$  = recommended

ND = none determined V = recomm. By vendor

 $\label{eq:by-product} {\tt By-product = reaction by-} \quad {\tt SKN = skin}$ 

product, TSCA inventory TS = trade secret status not required under R = recommended

40 CFR part 720.30(h-2) MST = mist

STEL = short term exposure NT = not tested

-			
-	7	mı.	-

.....

All chemical substances in this material are included on or exempted from listing on the TSCA inventory.

\*